



This product complements our chiller range and is designed for high transit areas or factories where forklifts and trolleys are used.

This water chiller is suitable for connection to one aquaBUBBLER. It is extremely robust and has heavy duty capacity.

Australian designed and manufactured

Water Reservoir:

The WR45 supplies 26 litres of chilled water per hour. It has a 2-litre water storage tank.

This “out of the way” water cooler is very versatile and can be installed in the roof or with in a cavity in a wall.

Refrigeration:

The system uses 275gms of refrigerant R22. It is non- toxic, non-flammable and environmentally sympathetic.

Water Connections:

Water Inlet – 6.4mm (1/4”) copper tube

Water Outlet – 6.4mm (1/4”) copper tube

Thermostat Control:

The thermostat is factory pre-set.

Compressor:

1/4 HP capacity, 370 watts.

The compressor is hermetically sealed for silent running.

Condenser:

The condenser is of copper and expanded aluminium fin.

Electrical:

240 volts, 50Hz.

A2 metre house cable and 3 pin plug is supplied.

Full load current is 2.69 amps.

Performance to ARI 1010-94 Standard:

Water Inlet – 26.7°C

Water Outlet – 10°C

Ambient Air – 32.2°C.

Packed Weight and Dimensions:

33 kgs

50cm long x 20cm wide x 60cm high

Warranty:

Twelve months comprehensive coverage

Five years for compressor replacement

Installation note:

The unit must be installed vertically and there must be a 75mm clearance on all sides to facilitate air flow.

Water fittings are supplied.

